1220

Ultra compact DIN rail mounted 1Q DC Drive. Non-isolated electronics providing up to 12.2A output current, suitable for DC motors up to 1.8kW output power.

Technical Data

The 1220 is one of the Sprint Electric 340/680/1220 SERIES of products

Ratings			
Show	• entries		
Search:			
AC Supply Range	Typical Max Armature Voltage	Max Continuous Armature Current	Nominal Power
100 to 130v	90v	12.2A	0.75KW / 1HP
200 to 264v	180v	12.2A	1.8KW / 2HP
Showing 1 to 2 of 2 entries			
PreviousNext			
Dimensions			
Show	- entries		
Search:			
Height	Width		Depth
105mm	45mm		120mm
Showing 1 to 7	1 of 1 entries		
PreviousNext			
AT A GLANCE			
 -1220 controller for DC motors rated up to 12.2 Amps (1.8KW/2HP) -DIN rail mounting -Easy to access drive adjustments -Plug-on screw terminals -Small footprint -UL, CuL and CE approved 			

TECHNICAL HIGHLIGHTS

-Switch selectable Tach or Armature voltage feedback -Adjustable IR compensation for improved AVF speed regulation -Selectable dual voltage ac supply -Aux speed trim input available in AVF mode -Plug in terminals -Can also drive universal motors

USER ADJUSTABLE

-Ramp -Max motor speed -Min motor speed -IR comp -Max motor current